

2820

The summit of
matrix printing



HIGHLIGHTS AT A GLANCE:

- Up to 1.000 characters / sec.
- Up to 50,000 pages / month
- Long-lasting print head
- Up to 5 copies
- Industrial housing
- Metal tear-off edge
- Ethernet interface with IPv6 support
- Coax interface with IPDS support





| | Tally Dascom 2820 | Oki ML4410 |
|----------------------------------|---------------------------|------------------------------|
| Print head | | |
| Pins | 24 | 2x 9 |
| Lifetime | 750 mio. | n.a. |
| Print speed | | |
| High Speed Draft @ 10 cpi | 1.000 cps | 1.066 cps |
| Draft @ 10 cpi | 833 cps | 800 cps |
| LQ/NLQ @ 10 cpi | 278 cps (LQ) | 200 cps (NLQ) |
| Interfaces | | |
| Ethernet | x (IPv6) | opt. |
| USB | x | - |
| Parallel | opt. | x |
| Serial | opt. | x |
| Usage | | |
| Memory | 256 kB | 56 kB |
| Ribbon | 20 mio. characters | 15 mio. characters |
| Emulations | | |
| Epson ESC P | x | x |
| IBM Proprinter | x | x |
| Print media | | |
| Copies | 1 original + 5 copies | 1 original + 9 copies |
| Print width | 76 - 420 mm | 76 - 406 mm |
| Dimensions | | |
| W x D x H | 624 x 432 x 280 mm | 768 x 385 x 358 mm |
| MTBF | | |
| MTBF | 20.000 hours | 12.000 hours |
| Power consumption | | |
| Tension | 220 - 240 VAC | 220 - 240 VAC |
| Power consumption while printing | 90 W | max. 295 W |