

## MIP480



*Tally*

The MIP480 is an impact printer, designed primarily for delivery note printing in commercial vans and trucks. Connection is via computerised Fleet Management systems or Truck/In-vehicle computing solutions. With nominal 12-24 volt power source, it is ideally suited for truck operation where it can be powered from the vehicle's battery. It combines speed, operational flexibility and rugged reliability to offer an exceptional printer that is ideally suited for route delivery and other mobile applications.

A 110/230V power adapter is available for use in general power supply applications. With a 15,000 hour MTBF, 2 million character print head life and printer ribbons that can last up to six months in typical route delivery printing applications, the MIP480 vehicle printer is well suited for invoice

### Highlights at a glance:

- Fastest impact mobile printer available today for truck use
- Rugged construction
- Simple to change ribbon
- Comprehensive set of interfaces: Serial RS232, USB-2 and Bluetooth
- Easy paper loading
- 12-24 volts nominal for compatibility with a wide range of trucks
- Wide range of accessories

printing in industries such as food and beverage, wholesale auto parts, emergency services, waste and hazardous materials. The MIP480 is an attractive printer for use in the warehouse and public safety sectors. The MIP480 can print up to 480 characters per second (400 cps at 10 characters per inch) and its 24-wire print head produces exceedingly clear text and graphic output on up to 4-part continuous and single sheet forms.

The printer supports a variety of emulations including IBM® Proprinter® X24e, Epson® ESC/P2 emulations and Intermec 6920. The standard configuration supports a generous range of interfaces; RS-232 Serial, Bluetooth and USB-2.

### Configurations:

- **MIP480** Standard Product mit Bluetooth

## MIP480

<b>Print Speed</b>	600 cps (Fastest Draft); 400 cps (Draft), 133 cps (LQ) at 10 cpi
<b>Resolution</b>	up to 180 x 360 dpi
<b>Throughput</b> (ECMA 132)	321 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20, 24 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	300 million strokes
<b>Memory</b>	64 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional), Serial RS-232, USB 2.0 and Bluetooth 1.2
<b>Standard Emulation</b>	BM ProPrinter XL24E, Epson ESC P/2, Intermec 6820
<b>Fonts</b>	Draft, Courier, Roman, Sans Serif, Bold, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 9 Barcodes
<b>Consumables</b>	Ribbon: 4 million characters
<b>Standard Paper Handling</b>	Push tractor and friction
<b>Number of Copies</b>	1 original + 3 copies
<b>Paper Type</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Weight</b>	60 - 260 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 102 to 267 mm Length: 76 to 365 (cut sheet) Width: 102 to 267 mm (Continuous forms)
<b>Physical Weight</b>	6,2 kg
<b>Physical Size</b>	365 x 263 x 140 mm (W x D x H)
<b>Acoustic</b>	57 dB(A)
<b>Power Voltage</b>	12 -24 V DC for connection in vehicles; 100 - 240 V - 50/60 Hz for stationary usage
<b>Power Consumption</b>	150 W Printing; 7 Watt Stand-By, 2 Watt Slepp Mode, 0,3 W Power Off
<b>Temperature</b>	-20° to +60° C; 30% to 80% humidity (Printing) -30° to +65° C; 30% to 90% humidity (Storing)
<b>Workload</b>	20.000 pages per month
<b>MTBF</b>	15.000 hours
<b>Drivers</b>	Windows 2000/XP/Vista/7/8 and Server 2003/2008t

### DASCOM GB Limited

Hart House, Priestley Road

Basingstoke, Hampshire RG24 9PU

Tel: +44 1256 355130 – Fax: +44 1256 481400

info.gb@dascom.com – www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 